

Digital Watchdog Value Line Camera B362DIR

A&E Specifications Security System

Masterformat® Numbers and Titles
28 00 00 ELECTRONIC SAFETY AND SECURITY
28 20 00 ELECTRONIC SURVEILLANCE
28 23 00 VIDEO SURVEILLANCE
28 23 29 VIDEO SURVEILLANCE REMOTE DEVICES AND SENSORS

PART 1: GENERAL

1.01 GENERAL

- A. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll-free technical support phone number from the manufacturer. The phone number shall allow for technical assistance for either the dealer/installer or the end user at no charge for as long as the product is installed.
- D. All systems and components shall be provided with an explicit manufacturer warranty.

1.02 SUMMARY

A. The high resolution bullet camera B362DIR is the finest bullet camera with an affordable price. With its innovative features, sleek attractive design, and DW's patent-pending "No Fog and No Condensation" circuit, the camera is ideal for a wide range of video surveillance applications.

1.03 SUBMITTALS

- A. Manual
- B. Specification Sheet
- C. Brochure
- D. Magazine Advertisement

1.04 REFERENCES

- A. National Television System Committee (NTSC)
- B. Conformity for Europe (CE)
- C. Federal Communications Commission (FCC)
- D. Restriction of Hazardous Substances (RoHS)

Toll Free: 866 446 3595 / Fax: 813 888 9262

1.05 QUALITY ASSURANCE

A. With engineering and manufacturing facilities in Seoul, Korea and distribution and product support in the United States, DW offers a level of specialty in the manufacturing and deployment of analogue and IP video security technology that your business can rely on. In addition to our proven product offerings, we have taken service and technology to the next level with a substantial investment in additional skilled industry professionals, online service capabilities, and application support. We offer technical assistance from Monday to Friday 8:30 AM to 8:00 PM EST via a toll-free telephone number at no extra charge.

1.06 DELIVERY, STORAGE, HANDLING

- A. General: Delivery, storage, and handling of the Digital Watchdog Camera shall be in accordance with the manufacturer's recommendations.
- B. Ordering: The manufacturer's ordering instructions and lead-time requirements shall be followed in order to avoid installation delays.
- C. Delivery: The Digital Watchdog Camera shall be delivered in the manufacturer's original, unopened, undamaged container with identification labels intact.
- D. Storage and Protection: The Digital Watchdog Camera shall be stored and protected from exposure to harmful weather conditions and at the environmental conditions recommended by the manufacturer.

1.07 WARRANTY

- A. LABOR: For a period of two (2) years and one (1) year on LED from the date of original purchase, if the Value Line Bullet Camera is determined to be defective, the Warrantor will repair or replace the unit with new or refurbished product at its option, at no charge.
- B. PARTS: In addition, the Warrantor will supply replacement parts for a period of two (2) years and one (1) year on LED. To obtain warranty or out of warranty service, please call a technical support representative at 1-866-446-3595 Monday through Friday from 8:30 AM to 8:00 PM EST.
 - A purchase receipt or other proof of the date of the original purchase is required before warranty service is rendered. The warranty only covers failures due to defects in materials and workmanship which arise during normal use. This warranty does not cover damage which occurs in shipment or failures which are caused by products not supplied by the Warrantor or failures which result from accident, misuse, abuse, neglect, mishandling, misapplication, alteration, modification, faulty installation, set-up adjustments, improper antenna, inadequate signal pickup, maladjustment of consumer controls, improper operation, power line surge, improper voltage supply, lightning damage, rental use of the product or service by anyone other than an authorized repair facility or damage that is attributable to acts of God.
- C. LIMITS AND EXCLUSIONS: There are no express warranties except as listed above. The Warrantor will not be liable for incidental or consequential damages, including without limitation or damage to recording media, resulting from the use of these products or arising out of any breach of the warranty. All express and implied warranties, including the warranties of merchantability and fitness for particular purpose, are limited to the applicable warranty period set forth above.

Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above exclusions or limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state-to-state.

Toll Free: 866 446 3595 / Fax: 813 888 9262

PART 2: SPECIFICATIONS

2.01 FEATURES

- A. The Digital Watchdog Value Line Bullet Camera shall be equipped with a 1/3" Sharp CCD.
- B. The Value Line Bullet Camera shall produce 540 TV Lines in the horizontal direction for color images and 560 TV Lines for black-and-white images.
- C. The Value Line Bullet Camera shall have an auto iris vari-focal lens. The lens shall offer a focal length that varies from 3.3 to 12 millimeters. The lens shall detect the amount of light entering the lens and automatically open/close the iris to maintain appropriate exposure.
- D. The Value Line Bullet Camera shall be built with IR illuminators. The IR illuminators shall allow the camera to operate in complete darkness without being noticed by the human eye. The IR illuminators shall be able to brighten a distance of up to 85 feet.
- E. During the day, the Value Line Bullet Camera shall operate as a color camera, and the camera shall be capable of switching to black-and-white in low light conditions. At low light conditions, the Value Line Bullet Camera shall use ambient IR light to capture black-and-white images.
- F. The Value Line Bullet Camera shall be built with a BLC (Backlight Compensation) technology that automatically gives the camera the necessary light level compensation and provides a good image of the subject in the foreground when there is a bright source in the background. BLC is usually good when there is a subject of interest, like an ATM machine.
- G. The Value Line Bullet Camera shall be built with an advanced light compensation technology DRC (Dynamic Range Compressor). DRC shall particularly make dark spots in images more visible without overexposing the bright spots.
- H. The Value Line Bullet Camera shall be able to mask overly exposed light with its HME (Highlight Masking Exposure) technology. HME shall especially be effective when trying to capture a license plate.
- I. The Value Line Bullet Camera shall include an ICON-driven OSD (On-Screen Display) menu with a built-in joystick that will make programming quicker and easier.
- J. The Value Line Bullet Camera shall include a secondary video-BNC output with a cable and a video test output for easy installation.
- K. The Value Line Bullet Camera shall consume less power than an ordinary surveillance camera. The Value Line Bullet Camera shall be considered energy saving.
- L. The Value Line Bullet Camera shall be outdoor/environmentally rated. It also shall be vandal and tamper resistant. The Value Line Bullet Camera shall have an Ingress Protection rating of 66.
- M. The Value Line Bullet Camera shall have no fog or condensation under any weather condition.
- N. The Value Line Bullet Camera shall be configurable for several foreign languages, other than English. The Value Line Bullet Camera shall include the following foreign languages: Korean, Chinese, French, and Spanish.
- O. The Value Line Bullet Camera shall meet or exceed the following design and performance specifications.

Toll Free: 866 446 3595 / Fax: 813 888 9262

2.02 CAMERA SPECIFICATIONS

A. Minimum Scene Illumination: 0.0 Lux

B. Lens Type: Vari-focal Auto Iris Lens
C. Focal Length: 3.3 ~ 12 millimeters
D. Lens: DC / MANUAL

E. Electronic Light Control Level: 0~100F. Direct Drive Level 0~31

G. Electronic Shutter Range: 1/60 ~ 1/100000

J. White Balance Mode: AWC / ATW / MANUAL / PUSH LOCK

K. Day & Night: Electronic Day and Night

L. Mirror: OFF / ON
 M. Sharpness: 0~49
 N. Gamma: 0.05~1.00
 O. Side Light Compensation: OFF / ON (0~50)
 P. HME: OFF / ON (0~55)

Q. DRC: OFF / INDOOR / OUTDOOR

R. Motion: OFF / ON

S. Privacy: OFF / ON (4 Programmable Zones)

T. Dead Pixel Cancellation: OFF / ON (0~254)U. PC Control: OFF / ON

V. On Screen Display: Built-in

W. Joystick: Built-in for OSD Control

2.03 VIDEO SPECIFICATIONS

A. Imaging Device: Sharp CCD
B. Image Size: 1/3-inch
C. Signal System: NTSC
D. Total Pixels: 811 X 508
E. Effective Pixels: 768 X 494

F. Scanning System: 525 Lines, 2:1 Interlace

G. Horizontal Frequency: 15,734 HzH. Vertical Frequency: 59.94HzI. Sync System: Internal

J. Horizontal Resolution: 540 TV Lines (Color), 560 TV Lines (B/W)K. Video Output: 1.0V [p-p] Composite Output, 75 Ohm

L. Signal-to-Noise Ratio: 50dB

2.04 ELECTRICAL SPECIFICATIONS

A. Power Requirement: Auto-Sensing Dual Voltage: DC 12V / AC 24V
B. Power Consumption: DC 12V: 1.7W, 141.7mA / AC 24V: 2.2W, 91.7mA
C. Power Consumption (LED ON): DC 12V: 4.1W, 341.7mA / AC 24V: 4.1W, 170.8mA

2.05 ENVIRONMENTAL SPECIFICATIONS

A. Environment: Indoor / Outdoor

B. Operational Temperature: $-10^{\circ}\text{C} \sim +55^{\circ}\text{C} (14^{\circ}\text{F} \sim 131^{\circ}\text{F})$

C. Operational Humidity: Less than 90%

Toll Free: 866 446 3595 / Fax: 813 888 9262

2.06 MECHANICAL SPECIFICATIONS

A. Construction: Metal CaseB. Mount: 3D Mount Bracket

C. Dimension: 80.6 (Height) X 251.2 (Width) millimeters 3.17 (Height) X 9.89 (Width) inches

D. Unit Weight: 1.02 pounds

2.07 CERTIFICATIONS

- A. CE
- B. FCC
- C. RoHS
- D. Meets Nema Type and IP66 Standards

2.08 WARRANTY

A. 2 Years, 1 Year on LED

2.09 MODEL NUMBERS

A. DWC-B362DIR

(Written May 12, 2011)

*Digital Watchdog is constantly developing product improvements. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Toll Free: 866 446 3595 / Fax: 813 888 9262