




### Dimensions (unit : mm)



### Summary

The C235T is a high performance box style camera that offers exceptional Wide Dynamic Range and sensitivity for harsh lighting environments, as well as high resolution imaging with its 1/3" PIXIM Seawolf CMOS sensor. PIXIM's technology allows each pixel to self-adjust in the same scene, giving terrific image quality. PIXIM revolutionizes the way video cameras capture and process images.

### Features

- 1/3" PIXIM Seawolf CMOS Sensor
- 690 Horizontal TV Lines
- TDN (True Day and Night/IR Cut Filter)
- 3D-DNR (3D Digital Noise Reduction)
- Powerful Wide Dynamic Range
- Ultra Low Light Sensitivity
- Smear Canceling Circuit
- AGC / BLC / AWB
- Programmable Privacy Zones (6) & Motion Detection
- Easy Icon Driven OSD Menu with Built-in Joystick
- Auto Sensing 12VDC/24VAC with Line Lock
- Secondary Video-BNC Output
- Compatible with C or CS Mount Lens

### Specifications

VIDEO	
Image Sensor	1/3" PIXIM Seawolf CMOS Sensor
Total Pixels	768 (H) x 548 (V)
Scanning System	525 Lines, 2 : 1 Interlace
Frequency	15.734KHz (H), 59.95Hz (V)
Synchronization	Internal / Line Lock
Horizontal Resolution	690 Effective Horizontal TV Lines
Minimum Illumination	F1.2 (30IRE): 0.22Lux [Color] F1.2 (30IRE): 0.01 Lux [B&W]
S/N Ratio	53dB (AGC off)
Video Output	CVBS: 1.0Vp-p / 75 Ω
OPERATIONAL	
Lens	MANUAL / DC
AE Preference	OUTDOOR / INDOOR
Wide Dynamic Range	LOW / NORMAL / MEDIUM / HIGH / CUSTOM
Auto Gain Control	LOW / MEDIUM / HIGH / CUSTOM
Star-Light	x2 ~ x64
White Balance Mode	ATW DESAT / PUSHLOK / MANUAL / ATW XTND / ATW NORMAL
Day & Night	AUTO / AUTO (EXT) / COLOR / B&W
Mirror	OFF / MIRROR / V-FLIP / ROTATE
Sharpness	-8 ~ 8
3D Digital Noise Reduction	MOVIE / INFO
Digital Zoom	1 ~ 12 / PAN (-100 ~ 100) / TILT (-100 ~ 100)
Privacy Zones	OFF / ON (6 Programmable Zones)
Baudrate	2400 ~ 38500
Protocol	PELCO-D / CPRO / CPRO1 / CPRO2
Language	ENGLISH
ENVIRONMENTAL	
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	Less than 90% (Non-Condensing)
Storage Temperature	-20°C ~ 70°C (-4°F ~ 158°F)
ELECTRICAL	
Power Requirement	Dual (12VDC & 24VAC)
Power Consumption	12VDC: 2.3W, 191.7mA 24VAC: 2.8W, 116.7mA
MECHANICAL	
Housing Material	Aluminum
Dimensions	119.7 x 58.8 mm (4.71 x 2.31 in)
Weight	0.6 lbs

\*Specification is subject to change without prior notice.