

Digital Watchdog Infinity Camera D2367WD

A&E Specifications Security System

Masterformat® Numbers and Titles
28 00 00 ELECTRONIC SAFETY AND SECURITY
28 20 00 ELECTRONIC SURVEILLANCE
28 23 00 VIDEO SURVEILLANCE
28 23 29 VIDEO SURVEILLANCE REMOTE DEVICES AND SENSORS

PART 1: GENERAL

1.01 GENERAL

- A. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll-free technical support phone number from the manufacturer. The phone number shall allow for technical assistance for either the dealer/installer or the end user at no charge for as long as the product is installed.
- D. All systems and components shall be provided with an explicit manufacturer warranty.

1.02 SUMMARY

A. Our Infinity DSP Series ensures excellent color sensitivity and high resolution in both day and night applications. The technology utilizes Star-Light, EWDR, DIS, and other great features to help produce clear 560 TVL images. Super Vision at Anytime, Anywhere.

1.03 SUBMITTALS

- A. Manual
- B. Specification Sheet
- C. Brochure

1.04 REFERENCES

- A. National Television System Committee (NTSC)
- B. Conformity for Europe (CE)
- C. Federal Communications Commission (FCC)
- D. Restriction of Hazardous Substances (RoHS)

Toll Free: 866 446 3595 / Fax: 813 888 9262

1.05 QUALITY ASSURANCE

A. With engineering and manufacturing facilities in Seoul, Korea and distribution and product support in the United States, DW offers a level of specialty in the manufacturing and deployment of analogue and IP video security technology that your business can rely on. In addition to our proven product offerings, we have taken service and technology to the next level with a substantial investment in additional skilled industry professionals, online service capabilities, and application support. We offer technical assistance from Monday to Friday 8:30 AM to 8:00 PM EST via a toll-free telephone number at no extra charge.

1.06 DELIVERY, STORAGE, HANDLING

- A. General: Delivery, storage, and handling of the Digital Watchdog Camera shall be in accordance with the manufacturer's recommendations.
- B. Ordering: The manufacturer's ordering instructions and lead-time requirements shall be followed in order to avoid installation delays.
- C. Delivery: The Digital Watchdog Camera shall be delivered in the manufacturer's original, unopened, undamaged container with identification labels intact.
- D. Storage and Protection: The Digital Watchdog Camera shall be stored and protected from exposure to harmful weather conditions and at the environmental conditions recommended by the manufacturer.

1.07 WARRANTY

- A. LABOR: For a period of five (5) years and one (1) year on LED from the date of original purchase, if the Digital Watchdog Camera is determined to be defective, the Warrantor will repair or replace the unit with new or refurbished product at its option, at no charge.
- B. PARTS: In addition, the Warrantor will supply replacement parts for a period of five (5) years and one (1) year on LED. To obtain warranty or out of warranty service, please call a technical support representative at 1-866-446-3595 Monday through Friday from 8:30 AM to 8:00 PM EST.
 - A purchase receipt or other proof of the date of the original purchase is required before warranty service is rendered. The warranty only covers failures due to defects in materials and workmanship which arise during normal use. This warranty does not cover damage which occurs in shipment or failures which are caused by products not supplied by the Warrantor or failures which result from accident, misuse, abuse, neglect, mishandling, misapplication, alteration, modification, faulty installation, set-up adjustments, improper antenna, inadequate signal pickup, maladjustment of consumer controls, improper operation, power line surge, improper voltage supply, lightning damage, rental use of the product or service by anyone other than an authorized repair facility or damage that is attributable to acts of God.
- C. LIMITS AND EXCLUSIONS: There are no express warranties except as listed above. The Warrantor will not be liable for incidental or consequential damages, including without limitation or damage to recording media, resulting from the use of these products or arising out of any breach of the warranty. All express and implied warranties, including the warranties of merchantability and fitness for particular purpose, are limited to the applicable warranty period set forth above.

Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above exclusions or limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state-to-state.

Toll Free: 866 446 3595 / Fax: 813 888 9262

PART 2: SPECIFICATIONS

2.01 FEATURES

- A. The Digital Watchdog Infinity Indoor Dome Camera shall be equipped with a 1/3" Sony Super II HAD CCD. The Infinity Indoor Dome Camera shall produce 560 TV Lines in the horizontal direction for color images and 580 TV Lines for black-and-white images.
- B. The Infinity Indoor Dome Camera shall have an auto iris vari-focal lens. The lens shall offer a focal length that varies from 3.3 to 12 millimeters. The lens shall detect the amount of light entering the lens and automatically open/close the iris to maintain appropriate exposure.
- C. During the day, the Infinity Indoor Dome Camera shall operate as a color camera, and the camera shall be capable of switching to black-and-white in low light conditions. At low light conditions, the Infinity Indoor Dome Camera shall use ambient IR light to capture black-and-white images.
- D. The Infinity Indoor Dome Camera shall include Digital Watchdog's Star-Light technology, which offers super low light imaging for any application.
- E. The Infinity Indoor Dome Camera shall be built with the 3D-DNR (3D Digital Noise Reduction) feature that filters the noise in video images, especially in low light conditions. The feature shall allow the camera to produce more color at night and to reduce the amount of storage space required to record the video.
- F. The Infinity Indoor Dome Camera shall be built with a DSS (Digital Slow Shutter) feature that increases the length of time the shutter remains open to collect any additional ambient light, illuminating typically dark environments.
- G. The Infinity Indoor Dome Camera shall be built with a EWDR (Electronic Wide Dynamic Range) feature that helps to get detailed information from the dark part of the image without saturation from the bright part by combining high shutter speed exposure in bright areas and low shutter speed exposure in dark areas into one clear image.
- H. The Infinity Indoor Dome Camera shall be able to mask overly exposed light with its HME (Highlight Masking Exposure) technology.
- I. The Infinity Indoor Dome Camera shall be built with a DIS (Digital Image Stabilizer) technology that removes the jitters caused by movement or vibrations. This feature shall reduce the amount of HDD Space needed to store recorded data.
- J. The Infinity Indoor Dome Camera shall include an ICON-driven OSD (On-Screen Display) menu with a built-in joystick that will make programming quicker and easier.
- K. The Infinity Indoor Dome Camera shall be configurable for several foreign languages, other than English. The Infinity Indoor Dome Camera shall include the following foreign languages: Korean, Japanese, Chinese, Russian, French, Spanish, and Italian.
- L. The Infinity Indoor Dome Camera shall include a secondary video-BNC output with a cable for easy installation.
- M. The Infinity Indoor Dome Camera shall meet or exceed the following design and performance specifications.

Toll Free: 866 446 3595 / Fax: 813 888 9262

2.02 CAMERA SPECIFICATIONS

A. Minimum Scene Illumination: F1.2: 0.14 Lux [Color], 0.03 Lux [B/W]

B. Lens Type: Vari-focal Auto Iris LensC. Focal Length: 3.3 ~ 12 millimeters

D. Lens Operation:

Iris Automatic (DC Drive)

Focus
Zoom
Manual
E. Brightness
O~99
F. Electronic Shutter Range: 1/60
1/100FLC

1/120~1/100000

G. BLC: OFF / ON

H. Auto Gain Control OFF / LOW / MIDDLE / HIGH

I. MAX_DR (EWDR): OFF / ON (0~20)
J. Starlight: OFF / AUTO (X2~X256)
K. Day & Night: Electronic Day and Night

L. Mirror: OFF / MIRROR / V-FLIP / ROTATE

M. Sharpness: 0~49

N. Gamma: 0.45~1.00 / USER

O. Freeze: OFF / ON P. Negative: OFF / ON

Q. 3D-DNR: OFF / LOW / MIDDLE / HIGH

R. Side Light Compensation: OFF / ON S. HME: OFF / ON T. DIS: OFF / ON

U. Privacy: OFF / ON (6 Programmable Zones)

V. Motion Detection: OFF / ON
W. Dead Pixel Cancellation: OFF / AUTO
X. Protocol: Pelco-D
Y. On Screen Display: Built-in

Z. Joystick: Built-in for OSD Control

2.03 VIDEO SPECIFICATIONS

A. Imaging Device: Super HAD II CCD

 B.
 Image Size:
 1/3-inch

 C.
 Signal System:
 NTSC

 D.
 Total Pixels:
 811 X 508

 E.
 Effective Pixels:
 768 X 494

F. Scanning System: 525 Lines, 2:1 Interlace

G. Horizontal Frequency: 15,734 HzH. Vertical Frequency: 59.94Hz

I. Sync System: Internal / Line Lock

J. Horizontal Resolution: 560 TV Lines (Color), 580 TV Lines (B/W)K. Video Output: 1.0V [p-p] Composite Output, 75 Ohm

L. Signal-to-Noise Ratio: 50dB

2.04 ELECTRICAL SPECIFICATIONS

A. Power Requirement: Auto-Sensing Dual Voltage: DC 12V / AC 24V
B. Power Consumption: DC 12V: 1.8, 150mA / AC 24V: 2.4W, 1.0A

Toll Free: 866 446 3595 / Fax: 813 888 9262

2.05 ENVIRONMENTAL SPECIFICATIONS

A. Environment: Indoor

B. Operational Temperature: $-10^{\circ}\text{C} \sim +55^{\circ}\text{C} (14^{\circ}\text{F} \sim 131^{\circ}\text{F})$

C. Operational Humidity: Less than 90%

2.06 MECHANICAL SPECIFICATIONS

A. Mount: Surface

B. Dimension: 110.3 (Height) X 134.9 (Width) millimeters 4.34 (Height) X 5.31 (Width) inches

C. Unit Weight: 0.8 pounds

2.07 CERTIFICATIONS

A. CE

B. FCC

C. RoHS

2.08 WARRANTY

A. 5 Years

2.09 MODEL NUMBERS

A. DWC-D2367WD

(Written May 12, 2011)

Toll Free: 866 446 3595 / Fax: 813 888 9262

^{*}Digital Watchdog is constantly developing product improvements. We reserve the right to modify product design and specifications without notice and without incurring any obligation.