

Digital Watchdog PIXIM Snapit Camera D4365T

A&E Specifications
Security System

Masterformat Numbers and Titles

28 00 00 ELECTRONIC SAFETY AND SECURITY

28 20 00 ELECTRONIC SURVEILLANCE

28 23 00 VIDEO SURVEILLANCE

28 23 29 VIDEO SURVEILLANCE REMOTE DEVICES AND SENSORS

PART 1: GENERAL

1.01 GENERAL

- A. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll-free technical support phone number from the manufacturer. The phone number shall allow for technical assistance for either the dealer/installer or the end user at no charge for as long as the product is installed.
- D. All systems and components shall be provided with an explicit manufacturer warranty.

1.02 SUMMARY

- A. Our simple to install housing series combined with our reliable camera technology series gives you a high quality camera in just a few minutes. All Snapit housings include both a built-in UTP and RS-485.

Our PIXIM Snapit Indoor Dome D4365T is powered by PIXIM's Seawolf Digital Imaging System. PIXIM's technology allows each pixel to self-adjust in the same scene, giving terrific image quality.

1.03 SUBMITTALS

- A. Manual
- B. Specification Sheet
- C. Brochure
- D. Magazine Advertisement

1.04 REFERENCES

- A. National Television System Committee (NTSC)
- B. Conformity for Europe (CE)
- C. Federal Communications Commission (FCC)
- D. Restriction of Hazardous Substances (RoHS)

1.05 QUALITY ASSURANCE

- A. With engineering and manufacturing facilities in Seoul, Korea and distribution and product support in the United States, DW offers a level of specialty in the manufacturing and deployment of analogue and IP video security technology that your business can rely on. In addition to our proven product offerings, we have taken service and technology to the next level with a substantial investment in additional skilled industry professionals, online service capabilities, and application support. We offer technical assistance from Monday to Friday 8:30 AM to 8:00 PM EST via a toll-free telephone number at no extra charge.

1.06 DELIVERY, STORAGE, HANDLING

- A. General: Delivery, storage, and handling of the Digital Watchdog Camera shall be in accordance with the manufacturer's recommendations.
- B. Ordering: The manufacturer's ordering instructions and lead-time requirements shall be followed in order to avoid installation delays.
- C. Delivery: The Digital Watchdog Camera shall be delivered in the manufacturer's original, unopened, undamaged container with identification labels intact.
- D. Storage and Protection: The Digital Watchdog Camera shall be stored and protected from exposure to harmful weather conditions and at the environmental conditions recommended by the manufacturer.

1.07 WARRANTY

- A. LABOR: For a period of five (5) years and one (1) year on LED from the date of original purchase, if the Digital Watchdog Camera is determined to be defective, the Warrantor will repair or replace the unit with new or refurbished product at its option, at no charge.
- B. PARTS: In addition, the Warrantor will supply replacement parts for a period of five (5) years and one (1) year on LED. To obtain warranty or out of warranty service, please call a technical support representative at 1-866-446-3595 Monday through Friday from 8:30 AM to 8:00 PM EST.

A purchase receipt or other proof of the date of the original purchase is required before warranty service is rendered. The warranty only covers failures due to defects in materials and workmanship which arise during normal use. This warranty does not cover damage which occurs in shipment or failures which are caused by products not supplied by the Warrantor or failures which result from accident, misuse, abuse, neglect, mishandling, misapplication, alteration, modification, faulty installation, set-up adjustments, improper antenna, inadequate signal pickup, maladjustment of consumer controls, improper operation, power line surge, improper voltage supply, lightning damage, rental use of the product or service by anyone other than an authorized repair facility or damage that is attributable to acts of God.

- C. LIMITS AND EXCLUSIONS: There are no express warranties except as listed above. The Warrantor will not be liable for incidental or consequential damages, including without limitation or damage to recording media, resulting from the use of these products or arising out of any breach of the warranty. All express and implied warranties, including the warranties of merchantability and fitness for particular purpose, are limited to the applicable warranty period set forth above.

Some states do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so the above exclusions or limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state-to-state.

PART 2: SPECIFICATIONS

2.01 FEATURES

- A. The Digital Watchdog PIXIM Indoor Dome Camera shall be equipped with a 1/3" Pixim Seawolf CMOS sensor. "Pixim's Digital Pixel System® technology delivers high resolution, crystal clear images that capture every aspect of any scene."
- B. The PIXIM Indoor Dome Camera shall produce 690 Effective TV Lines in the horizontal direction.
- C. The PIXIM Indoor Dome Camera shall have an auto iris vari-focal lens. The lens shall offer a focal length that varies from 3.3 to 12 millimeters. The lens shall detect the amount of light entering the lens and automatically open/close the iris to maintain appropriate exposure.
- D. During the day, the PIXIM Indoor Dome Camera shall operate as a color camera, and in low light conditions, the camera shall be capable of switching to black-and-white mode and using the ambient IR light that exist in its environment. The PIXIM Indoor Dome Camera shall be built with an IR cut filter. When the camera is operating in the day mode, the IR cut filter shall filter IR light for precise color reproduction. In the night mode, the filter shall be removed for greater light sensitivity.
- E. The PIXIM Indoor Dome Camera shall be built with the 3D-DNR (3D Digital Noise Reduction) feature that filters the noise in video images, especially in low light conditions. The feature shall allow the camera to produce more color at night and to reduce the amount of storage space required to record the video.
- F. The PIXIM Indoor Dome Camera shall be built with a Powerful Wide Dynamic Range imaging technology that captures all the details of any scene by eliminating underexposure or overexposure.
- G. The PIXIM Indoor Dome Camera shall be perfect for all indoor and outdoor lighting conditions with its Ultra Low Light Sensitivity.
- H. The PIXIM Indoor Dome Camera shall be built with a Smear Canceling Circuit that eliminates glares and reflections from the camera images.
- I. The PIXIM Indoor Dome Camera shall include an ICON-driven OSD (On-Screen Display) menu with a built-in joystick that will make programming quicker and easier.
- J. The PIXIM Indoor Dome Camera shall be configurable for several foreign languages, other than English. The PIXIM Indoor Dome Camera shall include the following foreign languages: Korean, Japanese, Chinese, Russian, French, Spanish, and Italian.
- K. The PIXIM Indoor Dome Camera shall be powerful yet energy efficient. It shall consume less power than an ordinary surveillance camera.
- L. The PIXIM Indoor Dome Camera shall include a built-in UTP cable and a built-in RS485 cable.
- M. The PIXIM Indoor Dome Camera shall include a secondary video-BNC output with a cable for easy installation.
- N. The PIXIM Indoor Dome Camera shall be quick and easy to install.
- O. The PIXIM Indoor Dome Camera shall meet or exceed the following design and performance specifications.

2.02 CAMERA SPECIFICATIONS

A.	Minimum Scene Illumination:	F1.2: 0.22 Lux [Color]
B.	Lens Type:	Vari-focal Auto Iris Lens
C.	Focal Length:	3.3 ~ 12 millimeters
D.	Day & Night	True Day and Night
E.	Brightness	-48~60
F.	AE Preference:	OUTDOOR / INDOOR
G.	BLC:	OFF / BLC (10~50)
H.	WDR:	LOW / NORMAL / MEDIUM / HIGH / CUSTOM
I.	AGC:	CUSTOM / LOW / MEDIUM / HIGH
J.	Starlight:	OFF / AUTO (X2~X64)
K.	Meter Zone:	ADJUST ZONE 1 / ADJUST ZONE 2
L.	Mirror	OFF / MIRROR / V-FLIP / ROTATE
M.	Sharpness:	-8~8
N.	Gamma:	0.25~1.0
O.	3D-DNR:	MOVIE / INFO
P.	D-Zoom:	X1.0~X8 -100~100 Pan -100~100 Tilt
Q.	Privacy:	OFF / ON (6 Programmable Zones)
R.	Motion Detection:	OFF / ON
S.	PC Control:	CAM ID (1~255) ID DISPLAY (OFF / ON) PROTOCOL (PELCO-D) BAUDRATE (2400 / 4800 / 9600 / 19200)
T.	On Screen Display:	Built-in
U.	Joystick:	Built-in for OSD Control

2.03 VIDEO SPECIFICATIONS

A.	Imaging Device:	Pixim Seawolf CMOS Sensor
B.	Image Size:	1/3-inch
C.	Signal System:	NTSC
D.	Total Pixels:	768 X 548
E.	Sync System:	Internal / Line Lock
F.	Horizontal Resolution:	690 Effective TV Lines
G.	Vertical Resolution	460 TV Lines
H.	Video Output:	CVBS X 2 (75 Ohm), UTP
I.	Digital Video Output:	8/10-bit ITU656
J.	Aspect Ratio:	4:3, 16:9
K.	Signal-to-Noise Ratio:	53dB

2.04 ELECTRICAL SPECIFICATIONS

A.	Power Requirement:	Auto-Sensing Dual Voltage: DC 12V / AC 24V
B.	Power Consumption:	DC 12V: 3.1W, 258.3mA / AC 24V: 3.2W, 133.3mA

2.05 ENVIRONMENTAL SPECIFICATIONS

A.	Environment:	Indoor
B.	Operational Temperature:	-10°C ~ +55°C (14°F ~ 131°F)
C.	Storage Temperature:	-20°C ~ +70°C (-4°F ~ 158°F)
D.	Operational Humidity:	Less than 90%

2.06 MECHANICAL SPECIFICATIONS

- A. Mount: Surface
- B. Dimension: 96.8 (Height) X 108 (Width) millimeters
3.81 (Height) X 4.25 (Width) inches
- C. Unit Weight: 0.507 pounds

2.07 CERTIFICATIONS

- A. CE
- B. FCC
- C. RoHS

2.08 WARRANTY

- A. 5 Years

2.09 MODEL NUMBERS

- A. DWC-D4365T

(Written May 12, 2011)

*Digital Watchdog is constantly developing product improvements. We reserve the right to modify product design and specifications without notice and without incurring any obligation.