




Summary


The V1312XW is our 12X fixed zoom vandal-proof dome camera built with a 3.6 \sim 44.3mm Varifocal Auto Iris Lens. The camera offers Electronic Day and Night, EWDR, 3D-DNR, DIS, and StarLight, making it suitable for any application. These advanced technologies combined with a 1/4" Ex-View HAD PS CCD will produce clear images in any environment.

Features

- 1/4" Sony EX-View HAD Double Scan CCD
- 560 TV Lines
- 3.6 ~ 44.3mm Varifocal Auto Iris Lens
- 12X Optical Zoom
- Electronic Day and Night Mode with Color Removal Circuit
- EWDR (Electronic Wide Dynamic Range)
- 3D-DNR (3D Digital Noise Reduction)
- Star-Light (Super Low Light Technology)
- DIS (Digital Image Stabilizer)
- Programmable Privacy Zones (12) & Motion Detection
- AGC / BLC / AWB
- On-Screen Menu Programming with Built-in Joystick
- Secondary Video-BNC Output for Easy Installation
- Auto Sensing 24 VAC/12 VDC with Line Lock
- RS-485 Built-in
- IP66 Certified

Dimensions (Unit: mm)





Specifications

| Model | | V1312XW |
|-----------------------------|--------------------------|--|
| Image | Device | 1/4" Sony EX-View HAD Double Scan CCD |
| | Pixels - Total | 811(H) X 508(V) |
| | Pixels - Effective | 768(H) X 494 (V) |
| Min. Scene Illumination | Color | F1.6, 50IRE: 1.2 Lux |
| | B/W | F1.6, 50IRE: 0.12 Lux |
| Functions | 3D-DNR | OFF / ON (Adaptive 3D and 2D) |
| | EWDR | OFF / ON |
| | Digital Zoom | x1 ~ x12 (x0.1 Step) |
| Resolutions | Color | 560 TV Lines |
| | B/W | 600 TV Lines |
| Video Output | Main Monitor | VBS 1.0Vp-p (75 Ohm Terminated) |
| Lens | Focal Length | f=3.6~44.3mm, F1.6 [Wide] / F2.0 [Tele] |
| | View Angle | Tele: 4.64°(H) x 3.52°(V); Wide: 54.44°(H) x 41.42°(V) |
| General | S/N Ratio | 52dB |
| | Sync System | Internal |
| | Shutter Speed | 1/50 ~ 1/10K·Set |
| Power | Requirement | DC12V, AC24V |
| | Consumption | DC12V: 2.8W, 283.3mA / AC24V: 3.2W, 133.3mA |
| Environmental Conditions | Operating Temperature | -10°C ~ 55°C |
| | Storage Temperature | -20°C ~ 70°C |
| | Operating Humidity | Under 90% (Non-Condensing) |
| Physical Specifications | Dimensions | 145 X 109.6 mm, 5.71 X 4.31 in |
| | Weight | N/A |
| | Certifications | CE, FCC, RoHS |
| | Nema Type | IP66 |

(*) Specification is subject to change without prior notice.



























