



-

STR

IP 2.1MP Snapit Indoor Dome Camera



Full HD



**Triplex Encoder** 





ONVIF



**Motion Detection** 




ΡοΕ



W. DIGITA



**Easy Installation** 



ONVIF (Open Network Video Interface Forum) compliant with ONVIF standards for increased flexibility and reduced total cost

PoE (Power over Ethernet) simplifies installation by connecting both power and network through a single cable




#### Wide View

covers a wide range of view (81°) and minimizes blind spots



Day & Night when light diminishes below a certain level, automatically switches to night mode to provide high quality black-and-white video images



# MEGAPIX Indoor Dome MD421D





#### Snapit Easy Installation



#### Summary

The MD421D MEGAPIX camera is a triple codec network camera that provides 1080P megapixel resolution at 30 frames per second. The camera's advanced technologies like Electronic Day and Night, 3D-DNR, and Double Shutter WDR will deliver the best images in any type of environment. And Power over Ethernet combined with our Snapit Housing, branded for its quick and easy installation procedure, allows you to view and control your MEGAPIX camera from anywhere in the world in just a few minutes.


#### Features

- ONVIF Compliant
- 2.1 Megapixels (1080P, 30fps)
- Triple Codecs (H.264, MJPEG, MPEG4) with Dual-Stream
- 1/2.8" CMOS Sensor (7% Larger Than 1/3" CMOS Sensor)
- 3.0~10.5mm Auto Focus Lens
- 8X Digital Zoom, 3X Optical Zoom
- Electronic Day and Night
- Power over Ethernet [PoE] & DC12V
- Two-Way Audio
- Local SDHC Card Remote Backup
- Web Server Built-in
- Double Shutter WDR (Wide Dynamic Range)
- 3D-DNR (3D Digital Noise Reduction)
- Programmable Privacy Zones (30) & Motion Detection

### Accessories (Optional)



Dimensions (unit : mm)



## Specifications

IMAGE	
mage Sensor	1/2.8" CMOS Sensor (7% Larger Than 1/3" CMOS Se
Total Pixels	2016 (H) X 1108 (V)
Vinimum Scene Illumination	F1.6 (30IRE): 0.5 Lux [Color]
	F1.6 (30IRE): 0.01 Lux [B&W]
ENS	0.0.40.5
Focal Length	3.0-10.5mm
_ens Type	Auto Focus
Digital Zoom / Optical Zoom	8X / 3X
Brightness	0~19
Shutter Mode	Auto, Manual
Digital Slow Shutter	Off, 2X, 3X, 4X
Shutter Speed	1/30, 1/60, 1/120
1	0~20
Auto Gain Control Back Light Compensation	0~20 Off, On
Day and Night	Auto, Day (Color), Night (B/W)
_ens Mode	Manual, DC, AF
Chroma (Hue & Saturation Settings)	0~20
Sharpness	0~10
Virror & Flip	Off, On
3D-Digital Noise Reduction	Off, Low, Middle, High
Privacy Zone	Off, On (30 Programmable Zones)
Notion Detection: Sensitivity	Low, Middle, High
Alarm Notifications	Notifications Via E-mail
NETWORK AN	802.2 Compliance 10/100 LAN
/ideo Compression Type	802.3 Compliance 10/100 LAN H.264, MPEG4, MJPEG (Super Fine~Low)
Resolution	1920X1080 (16:9) ~ 320X240 (4:3)
Frame Rate	Up to 30fps at All Resolutions
Streaming Capability	Dual-Stream at Different Rates and Resolutions
P	IPv4, IPv6
Protocol	TCP/IP, HTTP, DHCP, PPPoE, ICMP, ARP, RARP,
	RTSP, NTP, UDP, Multicast
Maximum User Access	20 Users
ONVIF Conformance	Yes
Web Viewer	OS: Windows XP / Vista / 7, MAC OS
	Browser: Internet Explorer, Chrome, Firefox, Safari
Video Management Software	NxMS. Pivot
Viemory Slot	Up to 24 Hour to Micro SDHC Card (4GB-32GB)
Nortory Olut	Card Not Included*
ENVIRONMENTAL	
Dperating Temperature/ Humidity	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	Less than 90% (Non-Condensing)
Storage Temperature	-20°C ~ 70°C (-4°F ~ 158°F)
Other Certifications	CE, FCC, RoHS
ELECTRICAL	
Power Requirement	DC 12V, PoE (IEEE802.3af Class 3)
Power Consumption	7.2W, 600mA
MECHANICAL	
Material	Plastic
	108 X 96.8 mm (4.25 X 3.8 in)
Dimensions	

\*Specification is subject to change without prior notice,

